

BEAUTY & QUALITY... NATURALLY BY



HANDSPLIT AND RESAWN Shakes

This high quality shake features a rough split face and sawn back. Popular on traditional, ranch, vacation homes, or non-residential structures designed to blend with the natural and/or rustic surroundings.





Beautiful • Durable • Insulative • Wind Resistant Withstands Thermal Shock • Impact Resistant • Light Weight Watkins Sawmills Ltd.

HANDSPLIT AND RESAWN Shakes

NUMBER 1 GRADE

Description:	Lengths 18-inch, thickness 1/2" (medium) and 3/4" (heavy) minimums; length 24-inch, thickness 3/8", 1/2" (medium) and 3/4" (heavy) minimums. Width 4" minimum and 14" maximum. Clear heartwood; 20% maximum flat grain.
Roof Exposure:	8-inch shakes - 7 1/2" maximum; 24-inch medium and heavy shakes - 10" maximum; 24-inch (3/8") shakes - 7 1/2" maximum (5" per UBC).
Wall Exposure:	Single course: 8" for 18-inch shake; 10 1/2" for 24-inch shake.
Recommended Use:	Double Course: 14" for 18-inch shake; 18" for 24-inch shake. For walls and roofs on 4:12 pitch and steeper where high quality
	appearance and performance is desired.

PREMIUM GRADE

Description:	Lengths 18-inch and 24-inch; width 4" minimum, thickness 1/2" (medium) and 3/4" (heavy). Clear heartwood; 100% edge grain; no defects
Roof Exposure:	7½" for 18-inch shake; 10" for 24-inch shake.
Wall Exposure:	Single course: 8" for 18-inch shake; 10 1/2" for 24-inch shake.
	Double Course: 14" for 18-inch shake; 18" for 24-inch shake.
Recommended Use:	For walls and roofs 4:12 pitch and steeper and where a premium quality product is needed or desired. The 100% edge grain requirement exceeds the national industry standard.

- Class A, B & C fire rating may be obtained by specifying Certi-Guard permanent fire retardant Certi-Split Handsplit and Resawn shakes.
- Certi-Last CCA treated shakes are available for added longevity. Contact the treatment company for treatment warranty information, accessory product requirements (including recommended fastener types) and application details for treated cedar material.
- Historical Projects: Watkins Sawmills Ltd. offers straight split/barn shake, and tapersplit products for historic accuracy. Ask your supplier for more details. Check CSSB technical manual for specific installation details.
- Products are manufactured and graded in accordance with UBC Standards No. 15-3 and/or CSA 0118.1.
- This is only a product description necessary for selection of materials and grades. For a new roof construction manual and/or wall manual please contact:

PO Box 314, Sumas, WA USA 98295 Telephone: (604) 462-7116 • Fax: (604) 462-7162 Email: Sales@watkinsawmills.com Toll Free: 1-800-663-8301



PO Box 3280, Mission, British Columbia V2V 4J4 Telephone: (604) 462-7116 • Fax: (604) 462-7162 Email: Sales@watkinsawmills.com Toll Free: 1-800-663-8301

Watkins Sawmills Ltd.